

04860.P539

Patent

UNITED STATES PATENT APPLICATION

for

ZOOMING CONTROLLER

Inventor

Daniel S. Venolia

Prepared By:

BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN
12400 Wilshire Blvd., 7th Floor
Los Angeles, California 90025-1026
(408) 720-8598

"Express Mail" mailing label number RB69920080X
Date of Deposit December 20, 1991

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under CFR 1.10 on the date indicated above and is addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

Coriolana De Vine
(Typed or printed name of person mailing paper or fee)
Coriolana De Vine
(Signature of person mailing paper or fee)

INS.

A11

FIELD OF THE INVENTION

The present invention pertains to the field of computer systems. In particular, the present invention relates to a method and device enabling a computer system to access a data field having a broad range and a fine resolution.

BACKGROUND OF THE INVENTION

A portion of the disclosure of this patent document contains material which is subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by any one of the patent disclosure, as it appears in the Patent and Trademark Office patent files or records, but otherwise reserves all copyright rights whatsoever.

Many types of data have a broad range and a fine resolution. For example, a videodisk is composed of a continuum of frames. The video disk can store up to a series of tens of thousands of frames. Thus, it has approximately five orders of magnitude. Likewise, electronic music composition requires controlling frequencies over the entire audible scale ranging from 15 to 20,000 hertz. Thus, three orders of magnitude are required to cover this range. Similarly, a five second digital audio clip may require five orders of magnitude to access each bit sample. These types of data are often linear in the sense that there are starting and ending points and many linked "frames" of data between the starting and ending points.

In order to access a videodisk, one needs frame accurate control over the entire medium. In other words, a user must be able to readily pick out one particular desired frame nestled among tens of thousands of frames. It becomes readily apparent that tasks such as adjusting key frames in a video film or manipulating audio samples, can be quite time consuming and frustrating. What is needed is a method or apparatus which lets the user find and access one particular desired piece of data which is located among a broad range of data.

2

In the past, this was accomplished by using scroll bars. However, scroll bars typically can handle only two orders of magnitude. Consequently, a scroll bar would need to be approximately twenty yards long in order to grant access to each frame of a video disk. This is impracticable.

5 Another method used in the prior art was to implement VCR-type controls. This allows the user control over the entire range of data. However, these types of controls lack selectivity. For example, it would be difficult for a user to stop precisely on one particular desired frame of a VCR
10 tape. The user would probably either overshoot or undershoot the desired frame and would probably go back and forth searching for that particular frame. What is needed is a method that gives the user control over a broad range, while giving the user random access to any particular piece of data within that range, especially at fine resolutions.

Yet another method used in the prior art to solve this problem is to
15 provide one control for magnification of the data and another control for scanning at the selected magnification. One product utilizing this technique is SoundEdit™ by Farallon Computing, Inc. However, this implementation has a drawback in that it requires two separate controls. A further disadvantage is that these two controls cannot be operated simultaneously. A
20 user has to change the magnification control independently from the navigation control. Such a system results in wasted time and effort. Thus, what is needed is a method for providing the user with easy and fluid interaction over varying magnification scales while simultaneously providing the user with the capability of scanning at that magnification scale.
25

SUMMARY AND OBJECTS OF THE INVENTION

In view of the problems associated with providing a user with control over a broad range of data, particularly linear data, one objective of the present invention is to provide the user with access of data down to very fine resolutions in a simple, natural, and cost effective method by utilizing a cursor positioning device such as a mouse, a trackball, touch tablet, joystick or other input device having the capability of providing control for movement in 2 dimensions (2 degrees of freedom) of a cursor.

Another objective is to increase the speed, accuracy, and selectivity of accessing data over a broad range by providing the user with easy and fluid interaction over varying magnification scales, while simultaneously providing the user with the capability of scanning the data at that magnification scale.

A method and device for accessing a broad data field having a fine resolution is described. The user selects a scale which can be varied by the user. The scale controls the magnification at which the user accesses and/or examines the data, and it may be considered that a selected magnification provides a particular range of the data (from one point to another point in the data). By moving the range to encompass different portions of the data field, the user can scan that portion of the data field. The present invention allows the user to simultaneously select the scale while moving the range over different portions of the data field. Thus, the user can "zoom in" and "zoom out" of different portions of the data field.

In one embodiment of the present invention, a particular piece of data within the broad data field can be accessed. First, the scale is selectively varied, thereby controlling a range within the data field. Then, the range is moved to encompass portions of the data field in which the piece of data resides. Next, the scale is successively decreased while, simultaneously, points successively closer to the location are kept with the range. The scale is decreased which increases the magnification (i.e., increasing the range's

resolution). The range is moved in this manner until the piece of data is actually accessed.

This is accomplished by using an input device having two degrees of freedom (e.g., a mouse, trackball, touch tablet, joystick, etc.). These two
5 degrees of freedom can be provided by movement along two different axes. For example, movement can be along the x and y-axes in a Cartesian coordinate system. Movement along one axis controls the selection of the scale, while movement along the other axis controls the particular range at that scale. In preferred embodiment, these axes can be remapped to control
10 the position of a cursor on a display screen, instead of the scale and range. In other words, the same input device can control either the position of a cursor or control the scale and range, simply by remapping the axes of the input device.

Other objects, features, and advantages of the present invention will be
15 apparent from the accompanying drawings and from the detailed description that follows below.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is illustrated by way of example, and not by way of limitation, in the figures of the accompanying drawings and in which like
5 reference numerals refer to similar elements and in which:

Figure 1 shows an example of the reduction of a full sized textual document for one embodiment of the present invention.

10 Figure 2 shows an example of one embodiment of the present invention for accessing a name from a phone book.

Figure 3 is a block diagram of the computer system upon which the present invention may be implemented.

15

Figure 4 is a block diagram of one embodiment wherein a mouse is utilized.

Figure 5 is a screen shot of the Zooming History Controller display.

20

Figure 6 are a series of screen shots of the Zooming History Controller display at various time scales ranging from decades to seconds.

25 Figure 7 depicts the auto-scrolling of the Zooming History Controller's timeline (allowing movement at a particular magnification through the data) and scale slider (allowing modification of the magnification at which the data can be scanned).

30 Figure 8 depicts auto-scrolling the Zooming History Controller's timeline.

Figure 9 depicts the Zooming History Controller's timeline when the user scrolls the timeline rapidly.

Figure 10 shows an alternate embodiment of the present invention as
5 applied to videodisks, the Zooming Videodisk Controller.

add
B.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
22

DETAILED DESCRIPTION

A method and apparatus for providing the user with easy and fluid interaction over varying magnification scales, while simultaneously
5 providing the user with the capability of scanning at that scale is described. In the following description, the present invention is implemented in reference to a Zooming History Controller and a Zooming Videodisk Controller.

It will be obvious, however, to one skilled in the art that the present invention can equally be applied to other implementations, as well. The
10 present invention can be used in conjunction with editing textual documents. This invention enhances the user's ability to view a textual document at any point in its creation history by enabling the user to control the historical view of a document that may have been around for years and modified on a time scale of seconds. Thus, the present invention enhances
15 the control of a document by showing the state of the document as it appeared at a selected time. Thus, the various edits to a document over time may be viewed; in other words, the document may be viewed at various stages of its creation such as a first draft, a second draft, etc.

On the other hand, the present invention can be used to graphically
20 reduce a document. By using the structure implicit in the document, a more semantically valid zoom can be achieved. Outlines can progressively collapse the most-indented items, showing just structure and spacing. Figure 1 shows the reduction of one page of a full sized textual document. The sequence of steps for a textual document as it is zoomed out are: squeezing out white
25 space, squashing all but the first lines of each paragraph, eliminating all but the first lines, eliminating all body text while leaving headings and sub-headings, then eliminating subheads, leaving headings only. Similarly, computer programs may also be edited in this manner.

The present invention also enhances accessing any collection of items
30 that has an order, such as a data set having a linked collection of items. For example, one embodiment is to access a phone directory as shown in Figure 2. Initially, twenty names at regular intervals from A to Z are displayed. An indicator portrayed as a triangle with an attached horizontal line, can slide up

and down this list. The user can implement another control to zoom in and out of this list. For example, as the user zoomed in on Collins, the display would show names sampled over A to N, then from B to D, then only the C's, and so on. The desired name is selected by moving the indicator while
5 zooming in on the desired name. Similarly, in another embodiment, the present invention can be used as a dictionary. The user starts with the most frequently used words and then "zooms in" on successively less frequently used words.

Another embodiment of this invention is to adjust a purely abstract
10 number for a frequency of a music synthesizer, simulation variable, etc. Horizontal mouse movement would choose the digit that is incremented or decremented by vertical mouse motion. Along these same lines, the present invention can also be applied to adjusting key frames in a video film or manipulating audio samples.

15 Referring to Figure 3, the computer system upon which the preferred embodiment of the present invention is implemented is shown as 100. 100 comprises a bus or other communication means 101 for communicating information, and a processing means 102 coupled with bus 101 for processing information. System 100 further comprises a random access memory (RAM)
20 or other dynamic storage device 104 (referred to as main memory), coupled to bus 101 for storing information and instructions to be executed by processor 102. Main memory 104 also may be used for storing temporary variables or other intermediate information during execution of instructions by processor 102. Computer system 100 also comprises a read only memory (ROM) and/or
25 other static storage device 106 coupled to bus 101 for storing static information and instructions for processor 102, and a data storage device 107 such as a magnetic disk or optical disk and its corresponding disk drive. Data storage device 107 is coupled to bus 101 for storing information and instructions. Computer system 100 may further be coupled to a display device 121, such as a
30 cathode ray tube (CRT) coupled to bus 101 for displaying information to a computer user. An alphanumeric input device 122, including alphanumeric and other keys, may also be coupled to bus 101 for communicating

information and command selections to processor 102. An additional user input device is cursor control 123, such as a mouse, a trackball, or cursor direction keys, coupled to bus 101 for communicating direction information and command selections to processor 102, and for controlling cursor

5 movement on display 121. This input device typically has two degrees of freedom in two axes, a first axis (e.g. x) and a second axis (e.g. y), which allows the device to specify any position in a plane. Another device which may be coupled to bus 101 is hard copy device 124 which may be used for printing instructions, data, or other information on a medium such as paper, film, or
10 similar types of media. Lastly, computer system 100 may be coupled to a device for sound recording and/or playback 125 such as an audio digitizer means coupled to a microphone for recording information. Further, the device may include a speaker which is coupled to a digital to analog (D/A) converter for playing back the digitized sounds.

15 In the currently preferred embodiment, computer system 100 is one of the Macintosh® family of personal computers such as the Macintosh® II manufactured by Apple® Computer, Inc. of Cupertino, California (Apple and Macintosh are registered trademarks of Apple Computer, Inc.). Processor 102 is one of the 68000 families of microprocessors, such as the 68000, 68020, or
20 68030 manufactured by Motorola, Inc. of Schaumburg, Illinois.

Mouse Control for the Present Invention

In one preferred embodiment of the present invention, a mouse is used. Figure 4 is a block diagram showing this embodiment. A mouse 130 is
25 a small hand-held box-like device which is coupled to the computer system 100 by a cable. A sensing mechanism 132 monitors the magnitude and direction of movement of mouse 130 and generates an output signal based thereon. This signal is sent to computer 100 for processing. After processing, computer 100 sends a signal to display device 121, which can effect a change in
30 the display corresponding to the mouse's movements. One or more push-down button(s) 131 are provided on the mouse 130. By depressing button(s) 131, a signal is sent to computer 100 that a desired location on display device

121 has been selected. The combination of moving mouse 130 to point a cursor to an object on the display screen and pressing the button(s) 131, while the cursor is pointing to the object to select the object, is called "point and click." An example of such a mouse can be found in U.S. Patent Number Re.

5 32,632.

In the currently preferred embodiment, the mouse not only controls a cursor position on a display screen, but it can also be made to control two different parameters. The way in which this is accomplished is by "remapping" the mouse's axes from controlling the x and y-axes cursor movements to, instead, controlling two parameters. When an axis of the mouse is remapped to a parameter, motion in that axis no longer moves the cursor. Instead, it controls the parameter.

By disassociating the axis of the mouse from the cursor, the mouse movement is not constrained by the edges of the display screen. Typically, when the cursor is positioned at the edge of a display screen, further movement of the mouse in the direction towards that edge will not effect any changes in the cursor position. With the present invention, when the axes of the mouse is remapped to controlling two parameters instead of the cursor position, the mouse may be moved in a range corresponding to the range of the two parameters rather than a range constrained by the boundaries of a display screen. In short, the present invention allows an input device with two degrees of freedom such as a mouse, trackball, touch pad, joystick, etc. to remap its axes to controlling two or more different sets of parameters.

However, it can be disconcerting to users to see the cursor remaining stationary while the mouse is moving. To overcome this, the cursor is hidden whenever either axis of the mouse is being remapped. The cursor reappears when the mouse control is shifted back to controlling the cursor position.

With the cursor hidden, one problem is that visual feedback for motion in the remapped axis is reduced. This makes that axis parameter somewhat harder to control. In an alternative embodiment, this problem is minimized by ignoring the mouse's motion in the remapped axis, unless it is

the dominant axis. The dominant axis is defined as being the axis that has been moved the most. Thus, only the parameter associated with the dominant axis is affected by the mouse's movements.

In one alternative embodiment, while an axis of the mouse is remapped, motion in that axis is not remapped, so the cursor retains its original position, until the mouse control is shifted back again to controlling the cursor. When both axes of the mouse are remapped to control two different parameters, the elements corresponding to those parameters will be highlighted as the parameters values change. When the mouse control is returned to controlling the cursor position, the cursor reappears over the last element affected.

The use of the mouse as a parameter control can also be supplemented by consistent visual reinforcement. For example, various icons can be used as indicators, pointers, and scrollers and various symbols may be used to represent certain aspects of the parameters being controlled.

Some parameters need an approximate setting. Others demand a more precise value. When controlling a remapped approximate parameter, each unit of motion of the mouse (~ one hundredth of an inch for the Macintosh™ mouse) can effect a change in the value of the parameter. For values that need to be controlled more precisely, one preferred embodiment is to reduce the mouse's motion units by eight times. Otherwise, the mouse's movements become too sensitive.

When values are assigned to parameters, the preferred embodiment is to make the mouse axes consistent with a positive or a negative change in that parameter's value. In other words, if a slider, scroll bar, or other graphic widget is used to represent the value that the mouse is controlling, the mouse axes are remapped to the dominant graphic axes. For example, if the slider is graphically oriented vertically, upward motion of the mouse moves the slider knob up. If a parameter value has no graphic representation in the system, a standard is applied consistently. One embodiment of this concept is to define rightward and upward movement to be "more" and leftward and downward to be "less".

In the preferred embodiment of the present invention, one parameter corresponds to a scale and the other parameter corresponds to an increment within the scale's range. The mouse is used to allow a user to simultaneously adjust both the control of the time scale and the control for scanning at the selected time scale. This is accomplished by reassigning the axes of the mouse from moving the cursor to controlling the time scale and the selected value at that time scale. By depressing the mouse button while the cursor is positioned over certain interface elements, the mouse is disengaged from the cursor. Instead, vertical movement of the mouse adjusts the time scale and horizontal mouse movement adjusts the selected value at that time scale. These parameters and their control will be explained in greater detail below.

The Preferred Embodiment - Zooming History Controller

The present invention as applied to the Zooming History Controller enables the user to browse the time domain at any time scale (magnification) or choose an incremental time value by successive refinement. The Zooming History Controller zooms on a time continuum for picking a date/time. This is accomplished by utilizing a mouse in the manner described above.

Figure 5 shows the Zooming History Controller "© Apple Computer, Incorporated". Basically, the user controls two values: the time scale and the selected time within that time scale. The time scale is controlled and shown by scale slider 11. Scale slider 11 also gives the current scale of timeline 14. The selected time is shown both in the column of fields 12 and by the indicator 13 on timeline 14.

Scale slider 11 is comprised of a vertical bar 15, a control knob 16, and arrow icons 17 and 18. By using the mouse or other cursor positioning means to position the cursor on vertical bar 15 and clicking the mouse button, control knob 16 highlights and repositions itself to the cursor location. If the cursor is positioned over control knob 16 and the mouse button is depressed and kept depressed, control knob 16 will track the vertical movements of the mouse by sliding up and down vertical bar 15 as the mouse is dragged up and down. Control knob 16 will continue to track the vertical mouse movements

until the mouse button is released. All the while that control knob 16 is being moved, the scale of timeline 14 is also correspondingly increased or decreased according to the vertical position of control knob 16.

Scale slider 11 can also be controlled by disassociating the mouse from
5 the cursor and moving the mouse in a vertical motion. If the cursor is
positioned over timeline 14 and the mouse button is depressed and kept
depressed, control knob 16 will be highlighted and will move correspondingly
to the vertical movement of the mouse. As control knob 16 slides up vertical
bar 15, the scale of timeline 14 increases (i.e., the amount of time covered by
10 the timeline increases), thereby decreasing the resolution of timeline 14. In
other words, the magnification at which one observes the data (timeline)
decreases. Conversely, as control knob 16 slides down vertical bar 15, the scale
of timeline decreases (i.e., the amount of time covered by the timeline
decreases), thereby increasing the resolution of timeline 14. As the scale of
15 timeline 14 changes, so too is the appearance of the timeline altered to reflect
the new scale.

Also, as control knob 16 moves up vertical bar 15, arrow icon 17 is
highlighted. Arrow icon 17 resides at the top of vertical bar 11 and points
straight up. As control knob moves down vertical bar 15, arrow icon 18 is
20 highlighted. Arrow icon 18 resides at the bottom of vertical bar 15 and points
straight down. The mouse's movements correspond to changes on the
display screen in units of pixels. However, each pixel unit changes the scale
value so slightly that control knob 16 might not move at all or might not
appear to move. By highlighting arrow icons 17 and 18, the association
25 between the mouse movement and the changes in scale is enhanced.

When the user releases the mouse button, the highlights and arrow
markers disappear, and the cursor reappears. Even if the mouse had been
moved vertically, the cursor reappears at the vertical position that it had
when the mouse button was first depressed. While the mouse button was
30 depressed, its vertical axis was decoupled from the cursor, and attached
instead to controlling the scale.

Figure 6 shows screen shots 25-30 of timeline 14 at various scales ranging from decades to seconds. The selected time is shown by the column of fields 12. The column of fields 12 is divided into rows 19-24, corresponding to convenient time fields, shown on the left-hand side, and the selected time units, shown on the right-hand side. Row 19 gives the year field (Year) and the selected year unit (1975). Row 20 gives the month field (Month) and the selected month unit (Jan). Row 21 gives the day field (Day) and the selected day unit (17th). Row 22 gives the hour field (Hour) and the selected hour unit (11 am). Row 23 gives the minute field (Minute) and the selected minute unit (:05). Row 24 gives the seconds field (Second) and the selected second unit (:13). Thus, the selected time in figure 3 is 13 seconds past 11:05 am of January 17, 1975.

It can be seen from screen shots 25-30 that timeline 14 looks different for different time scales, even though they represent the same selected time (i.e., 11:05:03 am January 17, 1975). Screen shot 25 depicts timeline 14 wherein the scale is in years. The selected field is depicted by shading the correct row 19-24 which corresponds to that particular scale. In screen shot 25, since the year field was selected, row 19 which corresponds to the year field, is shaded. The selected year, "1975", is shown on the right-hand side of row 19. Similarly, screen shot 26 depicts timeline 14 wherein the scale is in months. Accordingly, row 20 which corresponds to the month field, is shaded. Likewise, screen shots 27-30 depict timeline 14 wherein the scale is in days, hours, minutes, and seconds, respectively.

It can be seen from screen shots 25-30 of Figure 6 that as the scale is decreased, the resolution of timeline 14 is increased. Screen shot 25 shows the scale in years. Timeline 14 gives a range of approximately a decade. This allows the user to select a time to a resolution of years. Screen shot 26 shows the scale in months. Its timeline gives a range of approximately two years. This allows the user to select a time to a resolution of months instead of years. As the scale is decreased, the resolution increases. Screen shot 30 shows the scale in seconds. The range of timeline 14 for screen shot 30 covers a range of approximately 15 seconds. This allows the user to select a time to a

resolution of seconds. Thus, by simulating controlling the scale and value of the timeline, this embodiment allows the user to select a particular time, within seconds, from a range of a century.

The fields and the selected times are highlighted up to the current
5 finest-resolved selected time. Finer scales and units are dim, in comparison. This is illustrated in Figure 6. In screen shot 25, the selected scale is in years and the corresponding selected time unit is 1975. Thus, for that resolution, the "Year" field and the "1975" time unit are highlighted. As the resolution increases, as in screen shot 28, it can be seen that the prior selected fields (i.e.,
10 "Year", "Month", and "Day") and selected time units ("1975", "Jan", and "17th") remain highlighted. The current selected field ("Hour") and the current selected time unit ("11 am") are also highlighted. Yet the finer fields ("Minute" and "Second") and time units (":05 ." and ":13") which have yet to be selected by the user, remain dimmed.

15 As shown in Figure 6, indicator 13 includes an icon and a vertical line segment. The icon for indicator 13 resides halfway along the top of timeline 14. The vertical line segment extends from the bottom of the indicator icon, through timeline 14, to the bottom edge of timeline 14. The line segment intersects timeline 14 which corresponds to the selected time (also displayed
20 by the column of fields 12). As the scale is changed, the icon representing the indicator also changes to reflect the change in the scale. For example, the indicator icon representing the year scale, is in the shape of an hourglass, as shown in screen shot 25. The icon representing indicator 13 changes to the shape of a calendar for time scales of months and days, as shown in screen
25 shots 26 and 27, respectively. The icon representing indicator 13 changes to the shape of a clock for time scales of hours and minutes, as shown in screen shots 28 and 29, respectively. The icon representing indicator 13 changes to the shape of a stopwatch for the time scale of seconds.

Once the desired field has been selected, the user may then select any
30 time unit within that field. For example, in screen shot 26 of Figure 6, since the user has selected the month scale, the user may now select time units corresponding to months of the year (e.g., Jan. - Dec.). This is accomplished by

moving the mouse horizontally. (Remember that the scale was controlled by moving the mouse vertically.) Horizontal movement of the mouse controls the timeline and thus the position of access into the data at the selected scale/magnification.

- 5 Furthermore, once a desired field has been selected, the scale can, nevertheless, be changed within that field. For example, in screen shot 25 of Figure 6, even though the selected field is "Years", the user may change the scale of timeline 14 so long as what is displayed remains in years. Thus, timeline 14 may have an enlarged scale such that a decade is shown or may
10 have a reduced scale such that only half a dozen years are shown. Likewise, in screen shot 27, given the same field ("Day"), timeline 14 may have a scale encompassing 12 days (as shown) or may have a reduced scale encompassing only a couple of days.

- Figure 7 shows the manipulation of the timeline. The timeline is
15 manipulated by using the mouse to position the cursor over some point of timeline 14. When the mouse button is then "clicked", indicator 13 is repositioned to where the cursor is located. Indicator 13 and control knob 16 are highlighted. Arrows 17 and 18 appear above and below vertical bar 15 of scale slider 11. In addition, the cursor is removed from the display screen so
20 that it is no longer displayed.

- As the mouse is moved horizontally to the left and right, while still keeping the mouse button depressed, indicator 13 tracks the mouse's movements. In other words, indicator 13 (i.e., the icon and the vertical line segment) moves horizontally, left and right, across the width of timeline 14 to
25 track the mouse's movements.

- When the indicator is moved horizontally, it is constrained to stay within the boundaries of the timeline. If the indicator is moved to either the right or left ends of the timeline, an arrow symbol appears. Figure 8 shows the situation wherein indicator 13 is moved towards the left end of timeline
30 14. When indicator 13 reaches the left-most edge of timeline 14, arrow symbol 31 appears to the left of indicator 13 and points leftward. Similarly, if

the indicator is moved to the right-most edge of the timeline, an arrow symbol pointing to the right will appear to the right of the indicator.

When the indicator is moved to either edge of the timeline, in addition to the display of the arrow symbol, the timeline will scroll. The
5 timeline will scroll to the right if the indicator is moved to the left-most edge. Conversely, the timeline will scroll to the left if the indicator is moved to the right-most edge. Thus, in Figure 6, the "8 am", "Noon", "4 pm", etc. markers and their corresponding submarkers will be scrolled to the right. New
10 markers such as "4 am", "Midnight", "8 pm", etc. and their corresponding submarkers will successively appear from the left and be progressively scrolled to the right.

Furthermore, if the mouse is moved to the right or left, beyond the extremes of the timeline, the rate of the scrolling will increase. In addition, the arrow symbol will become longer. The farther that the mouse is moved
15 beyond the timeline extremes, the faster the scrolling rate and the longer the arrow symbol become. Figure 7 shows the situation wherein the mouse is moved to the left, beyond the left-most edge of timeline 14. It can be seen that indicator 13 is constrained within timeline 14. As the mouse is moved beyond that point, arrow symbol 31 becomes longer and timeline 14 is scrolled
20 faster as shown in Figure 9.

The timeline may also be scrolled without moving the indicator. This is accomplished by using two arrow icons which are positioned on either side of the timeline. Referring back to Figure 6, it can be seen that arrow icons 32 and 33 are respectively located to the immediate left and right of timeline 14.
25 Arrow icon 32 points to the left, and arrow icon 33 points to the right. If the user positions the cursor over one of these two arrow icons, depresses the mouse button, and keeps it depressed, several events happen simultaneously. The cursor disappears, the selected arrow icon is highlighted, arrow icons appear above and below scale slider 11, control knob
30 16 becomes highlighted, timeline 14 begins to scroll, and arrow symbols appear.

fields such as "Year", "Day", "Hour", "Minute", and "Second" cannot be accessed just by moving the mouse vertically.

Horizontal movement of the mouse, in this mode, scrolls timeline 14.

Note that indicator 13 remains stationary. Moving the mouse to the right

- 5 causes timeline 14 to scroll to the left and increments the selected time unit corresponding to that field. Moving the mouse to the left causes timeline 14 to scroll to the right and decrements the selected time unit corresponding to that field. The time units corresponding to fields that have higher resolutions than the selected field remain unchanged. Only those time units
10 which correspond to the selected field or a lower resolution field, change according to the scrolling of the timeline.

Thus, in Figure 5, this mode allows the user to scroll timeline 14 by

horizontal mouse movements. The currently selected field 20 is that of

"Month", which is highlighted. The currently selected time unit is "Jul" as

- 15 shown in field 20 and by indicator 13. If timeline 14 is scrolled to the right by moving the mouse to the left, the time unit would successively change to "June", "May", "April", etc. Eventually, if timeline 14 were scrolled far enough to the right, the time unit for the "Year" field 19 would change from its current "1962" to "1961". However, fields with higher resolutions (e.g.,
20 "Day" 21, "Hour" 22, "Minute" 23, and "Second" 24) than the currently selected field, along with their time units (e.g., "25th", "9 am", ":35 :", and ":04"), remain unchanged.

Figure 5 also shows arrow icons 34 and 35 straddling the selected

"Month" field 20. These arrow icons appear when the user selects this mode

- 25 (i.e., when the user "clicks" the cursor on a particular field). Arrow icon 34 is positioned to the immediate left of the selected field and points to the left. Arrow icon 35 is positioned to the immediate right of the selected field and points to the right. Arrow icon 34 is highlighted if timeline 14 is scrolled to the right. Arrow icon 35 is highlighted if timeline 14 is scrolled to the left.

- 30 A small bracket appears across the tip of any of the above discussed arrow icons (i.e., scale slider, timeline, or field arrow icons) if the parameter described by that arrow icon reaches an outer limit. The bracket indicates that

the parameter as represented by that icon has reached a limit and is being "blocked". The parameter remains blocked by the bracket until the parameter is pulled back from the limit.

For example, in Figure 5, if timeline 14 were constrained to not extend
5 after the date of July 1962, a bracket 36 would appear across the tip of field
arrow icon 35, if the user attempted to scroll after the date of July 1962. If
timeline 14 were constrained to not extend prior to the date of July 1962, a
bracket 37 would appear across the tip of field arrow icon 34, if the user
attempted to scroll prior to July 1962. Another example would be if the user
10 attempted to increase the scale to a field greater than a "Year", a bracket would
appear across the tip of scale arrow icon 17.

It would be apparent to those skilled in the art that the Zooming
History Controller can be linked to and access a database. Some sample
databases include musical compositions, films, textual documents, etc. For
15 example, by linking the Zooming History Controller to a musical
composition, the user may easily access one particular note among thousands
within the composition. This is accomplished by assigning each note to one
particular incremental time unit. The user may "zoom out" to locate the
general area wherein the desired note resides. The user then "zooms in" on
20 the desired note by successively decreasing the scale (increasing the
magnitude) while keeping the note within the range until the desired note is
located. Thus, the user may select a desired note by "zooming in" on it in the
same manner as one would "zoom in" on a particular date/time. In other
words, pieces of data within a database may be sequentially linked to
25 incremental time intervals of the Zooming History Controller. As example
of this concept is described in a following section entitled "Zooming
Videodisk Controller", wherein the frames of a videodisk (or film) may be
easily accessed.

30 Software Implementation

In one preferred embodiment of the present invention, the Zooming
History Controller is divided into two functional blocks of software code. One

block draws the contents of the Zooming History Controller based on a number of parameters. The other block changes the parameters based on the user's input. These blocks are referred to as the Draw and the Track routines, respectively.

- 5 The primary parameters to the Draw routine specify the currently selected time, the magnification, and the position of the indicator. Secondary parameters control the appearance and highlight of the various symbols and icons. This routine draws the Zooming History Controller off-screen and then copies it onto the display screen in order to minimize flashing and
- 10 visual inconsistency. The primary parameters sometimes require drawing parts of the timeline that are not accessible to the user. For example, the times before and after the timeline's outer limits.

- When the user "clicks" on one of the elements in the Zooming History Controller, the corresponding Track routine is invoked. Each Track routine
- 15 starts by altering the mouse behavior (from controlling the cursor position to controlling the parameters) and changing the secondary parameters to make symbols and icons appear and highlight. While the mouse button is depressed, the Track routine repeatedly changes the parameters in response to mouse movement and invokes the Draw routine. The Zooming History
- 20 Controller display is redrawn once more with the secondary parameters restored to normal. The mouse behavior is restored to controlling the cursor position.

- A copy of a software computer code "© Apple Computer, Incorporated" for the Zooming History Controller written for the Macintosh IIx™
- 25 computer is contained in Appendix A.

An Alternative Embodiment - Zooming Videodisk Controller

- Figure 10 shows an alternative embodiment of the present invention as applied to videodisks, the Zooming Videodisk Controller "© Apple
- 30 Computer, Incorporated". Basically, the Zooming Videodisk Controller operates in the same manner as the Zooming History Controller described above, with the following distinctions.

Similar to the Zooming History Controller, the user controls the time scale. However, in the Zooming Videodisk Controller, the user controls the selection of a video frame within that time scale, instead of a time unit.

The scale is controlled in the same manner as described in the

5 Zooming History Controller (i.e., scale slider 39 and vertical mouse movements disassociated from the cursor). An individual frame within that scale is selected in the same manner as a particular time unit was selected in the Zooming History Controller (i.e., manipulating the timeline or moving the indicator along the timeline).

10 In Figure 10, timeline 36 is divided into units of time which are further subdivided into individual frames on the videodisk. Thus, the present invention enables a user to select one particular frame among thousands of frames on a videodisk. The selected time and frame is shown by the position of indicator 38 along timeline 36 and also displayed by column of fields 38.

15 Column of fields 38 is comprised of rows 39-41. Row 39 is the "Minute" field and displays the currently selected minute in reference to the start of the videodisk. Row 40 is the "Second" field and displays the currently selected seconds in reference to the minutes. Row 41 is the "Frame" field and displays the currently selected frame in reference to the minutes and seconds.

20 Another embodiment is to include an "Hour" row in the column of fields, in the case of longer videodisks. In Figure 9, the currently selected frame corresponds to 20 minutes, 37 seconds and 16 frames into the videodisk, "20:37:16".

The frame corresponding to the selected time/frame is pulled from the
25 videodisk and displayed above timeline 36. This is illustrated by selected frame 37. Selected frame 37 is defined by column of fields 38 and the position of indicator 38 along timeline 36. As the user changes the selected time/frame, the corresponding frame is pulled from the videodisk and displayed.

30 Context frames 42 are sampled at regular intervals of the videodisk and displayed below timeline 36. Context frames 42 are displayed directly below the point of timeline 36 corresponding to their location on the timeline.

Vertical line segments connect context frames 42 to the corresponding point where they are located on timeline 36. Context frames 42 are used to give the user a reference point as to the section of the videodisk which is represented by that section of the timeline. Context frames 42 scroll in concert with
5 timeline 36 and adjust according to the scale. If the user positions the cursor over a context frame 42 and "clicks" the mouse button, the Zooming Videodisk Controller responds in the same manner as when timeline 36 is "clicked", with one exception. When the mouse is moved horizontally, both indicator 38 and timeline 36 track the mouse's movements. In one
10 embodiment, a graphic representation of the number of video frames between a pair of context frames 42 is shown to inform the user how much real time lies between that pair of context frames. In another embodiment, a graphic representation of the entire disk with a highlight of the timeline portion is used to inform the user what part of the video disk the current
15 selected frame 37 resides in.

One aspect of the Zooming Videodisk Controller is that it can be used to perform functions similar to the "jog/shuttle" functions found on some high-end videotape decks. To scan over a video sequence, the user can zoom in (i.e., decrease the scale) so that the whole scene is covered in timeline 36.
20 The user accomplishes this by adjusting the scale in reference to context frames 42. Indicator 38 is then dragged across timeline 36 to simulate the "jog" control, but at an adjustable scale.

The "shuttle" function is simulated by positioning indicator 38 to the beginning of the scene. Then, right scroll arrow icon 42 is selected via the
25 mouse. The scene "plays" as selected frames 37 are successively displayed. The scene "plays" at the rate determined by the current scale and the current scroll speed. The scene can be "played" in reverse by selecting left scroll arrow icon 43. The user can also "freeze frame" by changing the scroll speed to zero.

A preferred embodiment of the present invention will now be
30 described by referring to the flowchart shown in Figure 11. The first step 200 is to provide a data set (e.g., musical composition, film, textual document, etc.) to the computer system. Next, in step 201, a variable scale is provided to

the user. The y-axis of a mouse is remapped so that instead of controlling the vertical position of a cursor, vertical mouse movement controls the scale. As the scale is increased or decreased, the magnification level decreases or increases, respectively. In addition, a range is provided to display continuous

5 portions of the data set to the user in step 202. What is depicted by the range is dependent on the scale selected. The range will span a broad portion of the data set for a large scale. However, the resolution will be low. Conversely, if the scale is reduced, the magnification level increases and narrower portions of the data set are depicted by the range. As the scale is reduced, the
10 resolution increases. The range can be made to cover different portions of the data set for a given scale. This is accomplished by remapping the x-axis of the mouse so that instead of controlling the horizontal position of a cursor, horizontal mouse movement controls what portion of the data set is covered by the range.

15 In order to access a desired data point within a broad data set, the user starts in step 203 by selecting a relatively large scale. In step 204, the computer will change the span of the data set covered by the range according to the scale selected. Next, the user determines in step 205 whether the desired data point resides within the portion of the data set as depicted by the range. If so, then
20 step 207 may be skipped. Otherwise, step 207 requires the user to move the data set relative to the range so that the desired data point resides within the portion depicted by the range. This is typically done by moving the cursor positioning device (e.g. mouse) in a horizontal direction. Afterwards, a decision must be made in step 206. Is the desired data point accessible? If the
25 answer is "yes", then the desired data point is accessed and that is the end (step 208). If the answer is "no", then the scale must be decreased (as shown by step 209 by moving the cursor positioning device in a vertical direction) and the procedure must be repeated, starting back from step 205 until the scale is decreased enough so that the desired data point is accessible.